



POLYCOR F/R INSULATED DPC CAVITY CLOSER



DESCRIPTION:

Polycor F/R Insulated DPC Cavity Closer consists of a length of non combustible, flexible mineral wool slab fully bonded to a polyethylene damp proof course. The damp proof course has a 40 mm flange on each long side and a 100mm flange on one end.

PURPOSE:

Polycor F/R Insulated DPC Cavity Closers are a compression fit solution designed to reduce cold bridging around door and window frames along with minimising sound transmission along cavities of external walls.

BENEFITS:

- Meet full Building Regulations
- Fire, thermal and acoustic solution
- Simple to install
- Integral damp proof course
- Maintenance free

Specification

Dimensions



GAP

- 10mm
- 10mm
- 20mm
- 20mm
- 30mm
- 30mm
- 40mm
- 40mm
- 50mm
- 50mm
- 75mm
- 75mm
- 100mm
- 100mm

DIMENSIONS

25x100/165x1200mm
25x150/225x1200mm
35x100/165x1200mm
35x150/225x1200mm
45x100/165x1200mm
45x150/225x1200mm
55x100/165x1200mm
55x150/225x1200mm
65x100/165x1200mm
65x100/225x1200mm
90x100/150x1200mm
90x150/225x1200mm
120x100/165x1200mm
120x150/225x1200mm

[* Bespoke requests to customer specification available]

Standards & Performance:



The mineral wool insulation achieves a fire classification of Euroclass A1 and has a thermal conductivity of 0.035 W/mK. The DPC conforms to BS6515 (1984). Insulated DPC Cavity Closers conform to the 2000 Building Regulations (2006 edition).

The product has been independently tested adopting procedures and criteria from BS476 : part 20 : (1987) and achieved 1 hour fire resistance.

Fixing:



Polycor FR Insulated DPC Cavity Closer should be fitted during the building process prior to the installation of door and window frames.

This product should be fitted DPC side against the inner face of the outer brickwork, with one of the 40mm flanges folded against the door or window frame in the normal way, and with the other 40mm flange remaining flat against the inner face of the outer brickwork.

If more than one length of Insulated DPC Cavity Closer is required, it should be fitted with the 100mm flange at the bottom and with the next closer forming a close butt joint over the flange. The top of the Insulated DPC Cavity Closer should be sealed to the underside of the lintel or protected behind a cavity tray.

Handling/Storage:



Polycor FR Insulated DPC Cavity Closers are supplied in strong polyethylene bags for on site protection. Care should be taken to keep the product dry prior to installation.

Some local delamination may occur during handling. This does not detract from the performance of the product.



warringtonfire



sales@concept-conversions.co.uk



01933-673100



www.concept-conversions.co.uk



Unit 13, Trinity Centre,
Park Farm Industrial Estate,
Wellingborough, Northants,
NN8 6ZB.

